

ICE GENESIS Project Overview



The project leading to this application has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 824310. This document and its contents remain the property of the beneficiaries of the ICE GENESIS Consortium and may not be distributed or reproduced without the express written approval of the ICE GENESIS Coordinator.

This text reflects only the author's views and the Commission is not liable for any use that may be made of the information contained therein.

- 37 project partners
- 27 EU / 10 non-EU
- 10 countries



ICE GENESIS project overview

Creating the next generation of 3D simulation means for icing

 **Duration:** From 1st January 2019 until 31st December 2022

 **Coordinator:** AIRBUS OPERATION SAS

 **Budget:**

- Max EU Contribution: €11 964 300
- Total Estimated Project costs: €21 984 549
- Project effort in Person-months ~ 1858

 **Advisory board:** EASA, FAA, ADSE, AEROTEX,
AIRBUS Defense&Space, CSTB, DAHER, EMBRAER, PIAGGIO, SAFRAN nacelles

ICE GENESIS project overview

Top level objective

The top level objective of the ICE GENESIS project is to provide the European aeronautical industry with a validated new generation of:

3D icing engineering tools
(numerical simulation and Icing Wind Tunnels capabilities)

addressing

Regulation CS25 Appendix C (well-known icing environment)

Appendix O (SLD or Supercooled Large Droplet)

and snow conditions,

for safe, efficient and cost effective design and certification of future aircraft and rotorcraft.

Novelties in Europe : 3D ice scanning system
droplet temperature measurement
snow characterization and campaigns

ICE GENESIS project overview

Sub-objectives



Obj#1: Improve and validate existing **3D numerical tools** to predict ice accretion in Appendix C, Appendix O and Snow conditions.




Obj#2: Upgrade and calibrate **icing wind tunnels** to allow reproduction of:

- **Supercooled Large Droplets (SLD)** in FZDZ (Freezing drizzle) conditions.
- **Snow conditions**
- Additionally, to **assess the potential of current icing wind tunnels to represent SLD in FZRA (Freezing rain) conditions.**



Obj#3: Build a **large scale experimental database** on representative 3D configurations to be used as a solid reference (“ground truth”) for future numerical tools validation.

ICE GENESIS Organisation




WP DEPENDENCIES



Perform wind tunnel tests in liquid icing and snow conditions, in industrial environment (IWT and mockups)



Provide searchable database of experimental results for validation of numerical tools





SLD Test Capability



The project leading to this application has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 824310. This document and its contents remain the property of the beneficiaries of the ICE GENESIS Consortium and may not be distributed or reproduced without the express written approval of the ICE GENESIS Coordinator.

This text reflects only the author's views and the Commission is not liable for any use that may be made of the information contained therein.





SLD Test capability - Objectives



WP4 Instrumentation




WP4 Instrumentation



ICE GENESIS Public Dissemination Kit - July 2021

SLD Test capability - Calibration Methodology




Definition of the active spray nozzles layout on the SBS



Cloud homogeneity check




LWC measurements at the centerline of the t/s and in its reference cross-section



PSD/MVD measurements at the centerline of the t/s and in its ref. cross-section



Collect ice accretion shapes on reference NACA 0012 wing section




Check for potential spray nozzles malfunctionality and/or spray plume overlap effects on IG/CYLs



Perform the LWC measurements for the full envelope of spray nozzles water/air pressures ratio and assess the LWC cloud homogeneity


Perform the PSD/MVD measurements for the full envelope of spray nozzles water/air pressures ratio and assess the PSD/MVD cloud homogeneity.

Scan the reference ice accretion shapes for LWC checks and generate the facility SLD database after each calibration.



SLD Test capability – icing wind tunnels

RTA (1/4)







Test section	Size H (m) x W (m) x L (m)	Airspeed (m/s)	SAT (°C)	Altitude (m)
Reduced cross section	3.5 x 2.5 x 90.0 (1.7 x 2.9 x 3.0)	20 to 80	-2°C to -30°C.	sea level

SLD Test capability – icing wind tunnels

RTA (2/4)

■ Definition of icing wind tunnel calibration methods

- Three experimental test campaigns in Appendix O conditions using different instrumentation → intercomparison
- PSD and LWC measurements in cooperation with DLR, CU
 - Malvern Spraytec, 2D-S / FCDP, PIP, CAPS
 - WCM-2000, Nevzorov Probe, CU-IKP




Example PSD results for FZDZ and FZRA conditions (left) and LWC measurement comparison (top)

SLD Test capability – icing wind tunnels





RTA (3/4)

■ Improvement of experimental capability for FZDZ

- Investigations on achievable LWC and experimental testing of LWC reduction technologies
- Investigations on achievable PSD
 - Modifications, upgrades and adjustments on spray bar system and required settings
 - Measurements and experiments in IWT and with spray nozzle test rig
- Numerical and experimental investigations on **supercooled state** of large droplets
 - CFD simulations and experimental testing with NACA0012 wing
- Numerical and experimental investigations on cloud **uniformity**
 - Particle tracking CFD simulations and experimental tests with NACA0012 wing section
 - Uniformity measurements using the ice accretion grid



Preliminary PSD results for FZDZ
MVD > 40 μm





Droplet temperature and
uniformity investigations

SLD Test capability – icing wind tunnels

RTA (4/4)

- Test capability calibration in FZDZ conditions
 - Centreline PSD Measurements using the CAPS (DLR)
 - Droplet temperature measurements with RV
- Final SLD calibration test slot is scheduled for June 2021
 - Centreline PSD & PSD uniformity investigations
 - CAPS
 - LWC, LWC Uniformity
 - WCM-2000, (Nevzorov Probe)



SLD Test capability – icing wind tunnels

TsAGI AHT-SD (1/4)





Test section	Size H (m) x W (m) x L (m)	Airspeed (m/s)	SAT (°C)	Altitude (m)
Main	1.00 x 1.00 x 3.00	Up to 150	Up to -35	sea level

SLD Test capability – icing wind tunnels

TsAGI AHT-SD (2/4)

□ Spray nozzles selection and IWT performance improvement



Example of the PSD measured

- 7 types of nozzles were investigated, and corresponding PSDs were measured.
- On the basis of comparison with the regulatory requirements, SU12J Spraying Systems Co. nozzles were selected for:
 - ✗ the modernization of the AHT SD and
 - ✗ the update of the EU-1 water spraying systems.




SU12J SS nozzle adapted to the AHT SD water spraying manifold


SLD Test capability – icing wind tunnels

TsAGI AHT-SD (3/4)


□ AHT SD Calibration results (App.C)



Example of the particles sizes distribution




MVD dependence on the pressure ratio for different LWC values



SLD Test capability – icing wind tunnels

TsAGI AHT-SD (4/4)



- ✗ ⇒ injectors off
● ⇒ injectors on


☐ LWC uniformity check



Icing grid

☐ Way forward


- × March 2021 => AVI nacelle / AVI splitter tests in App. C conditions
- × March 2021 => LDO rescue hoist tests in App. C conditions
- × April 2021=> AHT SD Calibration for App. O conditions
- × Winter 2021-22=> Second step of the test campaign.



Icing intensity field – core with LWC variation less than 15%

SLD Test capability – icing wind tunnels

MinDef S1-ATF (1/3)



Test section	Size H (m) x W (m) x L (m)	Airspeed (m/s)	SAT (°C)	Altitude (m)
Omega	0.82 x 0.7 x 3	10 - 250	-65 - 15	s.l. - 10000



- No improvements on the facility performance have been executed during the ICE-GENESIS program.
- The calibration methodology has been reviewed, in agreement with the program requirement.

SLD Test capability – icing wind tunnels

MinDef S1-ATF (2/3)

- PSD vs EXTICE program

- × FSSP 2 μm – 95 μm combine with OAP 30 μm – 450 μm




- PSD vs. ICE-GENESIS

- × CAPS-38 \Rightarrow CAS 0,5 μm – 50 μm + CIP 7,5 μm – 950 μm

- Droplets temperature


- × RambowVision technique



SLD Test capability – icing wind tunnels

MinDef S1-ATF (3/3)


- Cloud homogeneity + LWC with icing grid vs. EXTICE program



- Cloud homogeneity vs. ICE-GENESIS
 - ✗ Check the spray bar functionality with the Icing grid
 - ✗ CU-iso-Kinetic probe and/or Nevzorov 2cup hot-wire device
- Cloud calibration activities scheduled on May 2021

SLD Test capability – icing wind tunnels

CIRA-IWT (1/4)




- 20 STAINLESS STEEL BARS, 50 NOZZLES LOCATIONS FOR EACH BAR, MAX 500 ACTIVE NOZZLES
- ON/OFF SOLENOID VALVE AT EACH SPRAYING LOCATION
- AIR AND WATER PRESSURE CONTROL IN EACH BAR
- TWO AIR-WATER SPRAY NOZZLES:
 - STANDARD FOR APP. C
 - SLD MOD#1 FOR FZDZ

Test section	Size H (m) x W (m) x L (m)	Airspeed (m/s)	SAT (°C)	Altitude (m)
MTS	2.35 x 2.25 x 7.00	40 - 120	-35 – Amb.	s.l. - 6500

SLD Test capability – icing wind tunnels



CIRA-IWT (2/4)

❑ Icing wind tunnel calibration methods – hot-wire LWC sensor selection



Test section	Size H (m) x W (m) x L (m)	Airspeed (m/s)	SAT (°C)	Altitude (m)
Full size	0.57 x 0.57 x 1.8	10 - 100	to -40	s.l. - 12000

1. Ext. Multi-Wire (a)
 2. Nevzorov 2-cup (b)
 3. Standard Nevzorov
 4. Robust probe (c)
 5. Ice Crystal Detector (d)
- × 30 spray conditions at -5 °C and three speed (40, 80, and 100 ms⁻¹)
 - × LWC sweep @ 20 μm, 100 μm and 250 μm
 - × MVDs sweep @ 0,5 g m⁻³ and 0,2 g m⁻³





CIRA would like to acknowledge:

- ❑ David Orchard and Gislain Chevette (NRC-AIWT) for providing facility time-slot
- ❑ Mengistu Wolde, Natalia Bliankinshtein and Leonid Nichman, collected and organized data from all 5 sensors used in this analysis, shared the NRC's ICD and Nevzorov data and their initial analysis as part of the GLAZEICE project funded by the NRC APDC program
- ❑ Christiane Voigt and Johannes Lucke (DLR) for providing Nevzorov 2-cup and processing its data

SLD Test capability – icing wind tunnels

CIRA-IWT (4/4)

❑ Improvement of experimental capability for FZDZ and FZRA





- 13 spray nozzles set ups have been investigated through PDI testing over a range of conditions including 3 prototype 3D printed nozzles.
- 3 candidate nozzle setups have been selected for FZDZ and FZRA cloud generation in CIRA-IWT. Preliminary wind tunnel tests are scheduled on week #19 (May 10 – 14, 2021).
- CIRA-IWT full calibration (FZDZ + FZRA) scheduled in July - November 2021

SLD Test capability – icing wind tunnels


CIAM C-2 (1/4)

- ❑ 2D design numerical pre-analysis to determine the shape of the channel



mono-dp = 2 mm $V_{outlet} = 180$ m/s

$r_{inlet} = 700$ mm Tube length = 7500 mm
(stand restrictions)




Multi-stage rectangular wind tunnel with stabilization sections

SLD Test capability – icing wind tunnels

CIAM C-2 (2/4)

- ❑ The layout scheme of the C-2 stand with IWT for SLD has been approved



Mock-up assembly of the first sections of the IWT was made






SLD Test capability – icing wind tunnels

CIAM C-2 (3/4)

- ❑ The unit for determining the flow characteristics of the injectors has been assembled




two types of air nozzles have been investigated



SLD Test capability – icing wind tunnels

CIAM C-2 (4/4)

- ❑ Computational studies to determine the spray bar geometry. Evaluation of the influence of the pylon shape on the aerodynamic characteristics of the collector



- The aerodynamic losses of the flow pressure during the passage of a collector with different pylon shapes are estimated
- In a non-stationary calculation, the effect of the "cut" of the trailing edge on the increase in flow turbulence and the spread of droplets is checked. **This modification is justified only for drops with a diameter of up to 80 microns (only for Appendix C).** For SLD, a pylon is used without a clipped trailing edge.

THANK YOU FOR YOUR INTEREST



The project leading to this application has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 824310. This document and its contents remain the property of the beneficiaries of the ICE GENESIS Consortium and may not be distributed or reproduced without the express written approval of the ICE GENESIS Coordinator. This text reflects only the author's views and the Commission is not liable for any use that may be made of the information contained therein.

